


TH Débits et dimensions

Cône creux, angle de pulvérisation petit à moyen, diamètres nominaux, 1" à 3", BSP ou NPT

Taraudage BSP NPT	Pulvérisateur numéro				K	L / MIN @ BAR								Diam. aprox. orifice Ø [mm]	Passage libre min. aprox. Ø [mm]	Dimensions [mm]				[kg]
		0,3 bar	1,5 bar	3 bar		0,2 bar	0,3 bar	0,5 bar	0,7 bar	1 bar	1,5 bar	2 bar	3 bar			A	B	C	D	
2	THF8516	63°	65°	65°	194	86,6	106	137	162	194	237	274	336	21,8	21,8	91,9	130	106	62,7	1,81
	THF10516	65°	67°	67°	239	107	131	169	200	239	293	338	414	25,4	25,4					
	THF12516	68°	70°	70°	285	127	156	201	238	285	349	403	493	29,0	29,0					
	THF14516	74°	79°	79°	330	148	181	234	276	330	405	467	572	32,1	32,1					
	THF17016	77°	80°	80°	387	173	212	274	324	387	474	548	671	35,3	35,3					
	THF19216	77°	80°	80°	438	196	240	309	366	438	536	619	758	38,5	36,5					
	THF20516	77°	83°	83°	467	209	256	330	391	467	572	661	809	41,3	36,5					
	THF23016	76°	83°	83°	524	234	287	371	439	524	642	741	908	44,5	36,5					
2 1/2	THF17020	85°	85°	85°	387	173	212	274	324	387	474	548	671	33,7	33,7	125	172	133	77,7	2,90
	THF19020	70°	73°	73°	433	194	237	306	362	433	530	612	750	36,1	36,1					
	THF20520	72°	75°	73°	467	209	256	330	391	467	572	661	809	37,3	37,3					
	THF23020	76°	78°	78°	524	234	287	371	439	524	642	741	908	40,1	40,1					
	THF28020	79°	80°	80°	638	285	349	451	534	638	781	902	1105	46,0	44,5					
	THF32020	83°	85°	85°	729	326	399	516	610	729	893	1031	1263	51,2	44,5					
	THF34020	87°	90°	90°	775	347	424	548	648	775	949	1096	1342	53,2	44,5					
	THF43520	92°	95°	95°	991	443	543	701	829	991	1214	1402	1717	61,9	44,5					
3	THF18524	58°	58°	58°	422	189	231	298	353	422	516	596	730	32,5	32,5	145	200	153	88,9	4,08
	THF23024	65°	65°	65°	524	234	287	371	439	524	642	741	908	36,5	36,5					
	THF28024	70°	70°	70°	638	285	349	451	534	638	781	902	1110	41,3	41,3					
	THF32024	65°	70°	70°	729	326	399	516	610	729	893	1030	1260	45,2	45,2					
	THF34024	68°	70°	70°	775	347	424	548	648	775	949	1100	1340	46,8	46,8					
	THF41224	75°	78°	78°	939	420	514	664	786	939	1150	1330	1630	53,6	53,6					
	THF46924	75°	80°	80°	1070	478	585	756	894	1070	1310	1510	1850	57,9	54,0					
	THF52624	78°	80°	80°	1200	536	657	848	1000	1200	1470	1700	2080	63,1	54,0					
THF56424	78°	80°	80°	1290	575	704	909	1080	1290	1570	1820	2230	65,9	54,0						

$$\text{Débit (l}_{\min}) = K \text{ bar}$$

Matériaux standard: Laiton, fonte gris, acier et 1.4401 (316).