


THW Débits et dimensions

Cône creux, grand angle de pulvérisation petit à moyen, diamètres nominaux, 1" à 3", BSP ou NPT

Taraudage BSP NPT	Pulvérisateur numéro				K	L / MIN @ BAR								Diam. aprox. orifice Ø [mm]	Passage libre min. aprox. Ø [mm]	Dimensions [mm]				[kg]
		0,3 bar	1,5 bar	3 bar		0,2 bar	0,3 bar	0,5 bar	0,7 bar	1 bar	1,5 bar	2 bar	3 bar			A	B	C	D	
2	THF8516	112°	115°	115°	194	86,6	106	137	162	194	237	274	336	21,8	21,8	91,9	130	114	70,6	1,81
	THF10516	120°	122°	122°	239	107	131	169	200	239	293	338	414	25,4	25,4					
	THF12516	119°	122°	122°	285	127	156	201	238	285	349	403	493	29,0	29,0					
	THF14516	122°	125°	125°	330	148	181	234	276	330	405	467	572	32,1	32,1					
	THF17016	125°	125°	125°	387	173	212	274	324	387	474	548	671	35,3	35,3					
	THF19216	125°	125°	125°	438	196	240	309	366	438	536	619	758	38,5	36,5					
	THF20516	125°	125°	125°	467	209	256	330	391	467	572	661	809	41,3	36,5					
	THF23016	125°	125°	125°	524	234	287	371	439	524	642	741	908	44,5	36,5					
2 1/2	THF17020	117°	120°	120°	387	173	212	274	324	387	474	548	671	33,7	33,7	125	172	143	88,1	2,90
	THF19020	117°	120°	120°	433	194	237	306	362	433	530	612	750	36,1	36,1					
	THF20520	117°	120°	120°	467	209	256	330	391	467	572	661	809	37,3	37,3					
	THF23020	123°	125°	125°	524	234	287	371	439	524	642	741	908	40,1	40,1					
	THF28020	128°	130°	130°	638	285	349	451	534	638	781	902	1110	46,0	44,5					
	THF32020	128°	130°	130°	729	326	399	516	610	729	893	1030	1260	51,2	44,5					
	THF34020	128°	130°	130°	775	347	424	548	648	775	949	1100	1340	53,2	44,5					
	THF43520	128°	130°	130°	991	443	543	701	829	991	1210	1400	1720	61,9	44,5					
3	THF18524	122°	122°	122°	422	189	231	298	353	422	516	596	730	32,5	32,5	145	200	173	109	4,08
	THF23024	122°	122°	122°	524	234	287	371	439	524	642	741	908	36,5	36,5					
	THF28024	122°	122°	122°	638	285	349	451	534	638	781	902	1110	41,3	41,3					
	THF32024	125°	125°	125°	729	326	399	516	610	729	893	1030	1260	45,2	45,2					
	THF34024	125°	125°	125°	775	347	424	548	648	775	949	1100	1340	46,8	46,8					
	THF41224	128°	130°	130°	939	420	514	664	786	939	1150	1330	1630	53,6	53,6					
	THF46924	129°	132°	135°	1070	478	585	756	894	1070	1310	1510	1850	57,9	54,0					
	THF52624	129°	132°	135°	1200	536	657	848	1000	1200	1470	1700	2080	63,1	54,0					
	THF56424	129°	132°	135°	1290	575	704	909	1080	1290	1570	1820	2230	65,9	54,0					

$$\text{Débit (l}_{\min}) = K \text{ bar}$$

Matériaux standard: Laiton, fonte gris, acier et 1.4401 (316).

Revised 7/14/99