


THW Débits et dimensions

Cône creux, grand angle de pulvérisation petit à moyen, diamètres nominaux, 1" à 3", BSP ou NPT

| Taraudage BSP NPT | Pulvérisateur numéro |  | | | K | L / MIN @ BAR | | | | | | | | Diam. aprox. orifice Ø [mm] | Passage libre min. aprox. Ø [mm] | Dimensions [mm] | | | | [kg] |
|-------------------------|-------------------------|---|------------|----------|------|---------------|------------|------------|------------|----------|------------|----------|----------|-----------------------------------|--|-----------------|-----|-----|------|------|
| | | 0,3 bar | 1,5 bar | 3 bar | | 0,2 bar | 0,3 bar | 0,5 bar | 0,7 bar | 1 bar | 1,5 bar | 2 bar | 3 bar | | | A | B | C | D | |
| 2 | THF8516 | 112° | 115° | 115° | 194 | 86,6 | 106 | 137 | 162 | 194 | 237 | 274 | 336 | 21,8 | 21,8 | 91,9 | 130 | 114 | 70,6 | 1,81 |
| | THF10516 | 120° | 122° | 122° | 239 | 107 | 131 | 169 | 200 | 239 | 293 | 338 | 414 | 25,4 | 25,4 | | | | | |
| | THF12516 | 119° | 122° | 122° | 285 | 127 | 156 | 201 | 238 | 285 | 349 | 403 | 493 | 29,0 | 29,0 | | | | | |
| | THF14516 | 122° | 125° | 125° | 330 | 148 | 181 | 234 | 276 | 330 | 405 | 467 | 572 | 32,1 | 32,1 | | | | | |
| | THF17016 | 125° | 125° | 125° | 387 | 173 | 212 | 274 | 324 | 387 | 474 | 548 | 671 | 35,3 | 35,3 | | | | | |
| | THF19216 | 125° | 125° | 125° | 438 | 196 | 240 | 309 | 366 | 438 | 536 | 619 | 758 | 38,5 | 36,5 | | | | | |
| | THF20516 | 125° | 125° | 125° | 467 | 209 | 256 | 330 | 391 | 467 | 572 | 661 | 809 | 41,3 | 36,5 | | | | | |
| | THF23016 | 125° | 125° | 125° | 524 | 234 | 287 | 371 | 439 | 524 | 642 | 741 | 908 | 44,5 | 36,5 | | | | | |
| 2 1/2 | THF17020 | 117° | 120° | 120° | 387 | 173 | 212 | 274 | 324 | 387 | 474 | 548 | 671 | 33,7 | 33,7 | 125 | 172 | 143 | 88,1 | 2,90 |
| | THF19020 | 117° | 120° | 120° | 433 | 194 | 237 | 306 | 362 | 433 | 530 | 612 | 750 | 36,1 | 36,1 | | | | | |
| | THF20520 | 117° | 120° | 120° | 467 | 209 | 256 | 330 | 391 | 467 | 572 | 661 | 809 | 37,3 | 37,3 | | | | | |
| | THF23020 | 123° | 125° | 125° | 524 | 234 | 287 | 371 | 439 | 524 | 642 | 741 | 908 | 40,1 | 40,1 | | | | | |
| | THF28020 | 128° | 130° | 130° | 638 | 285 | 349 | 451 | 534 | 638 | 781 | 902 | 1110 | 46,0 | 44,5 | | | | | |
| | THF32020 | 128° | 130° | 130° | 729 | 326 | 399 | 516 | 610 | 729 | 893 | 1030 | 1260 | 51,2 | 44,5 | | | | | |
| | THF34020 | 128° | 130° | 130° | 775 | 347 | 424 | 548 | 648 | 775 | 949 | 1100 | 1340 | 53,2 | 44,5 | | | | | |
| | THF43520 | 128° | 130° | 130° | 991 | 443 | 543 | 701 | 829 | 991 | 1210 | 1400 | 1720 | 61,9 | 44,5 | | | | | |
| 3 | THF18524 | 122° | 122° | 122° | 422 | 189 | 231 | 298 | 353 | 422 | 516 | 596 | 730 | 32,5 | 32,5 | 145 | 200 | 173 | 109 | 4,08 |
| | THF23024 | 122° | 122° | 122° | 524 | 234 | 287 | 371 | 439 | 524 | 642 | 741 | 908 | 36,5 | 36,5 | | | | | |
| | THF28024 | 122° | 122° | 122° | 638 | 285 | 349 | 451 | 534 | 638 | 781 | 902 | 1110 | 41,3 | 41,3 | | | | | |
| | THF32024 | 125° | 125° | 125° | 729 | 326 | 399 | 516 | 610 | 729 | 893 | 1030 | 1260 | 45,2 | 45,2 | | | | | |
| | THF34024 | 125° | 125° | 125° | 775 | 347 | 424 | 548 | 648 | 775 | 949 | 1100 | 1340 | 46,8 | 46,8 | | | | | |
| | THF41224 | 128° | 130° | 130° | 939 | 420 | 514 | 664 | 786 | 939 | 1150 | 1330 | 1630 | 53,6 | 53,6 | | | | | |
| | THF46924 | 129° | 132° | 135° | 1070 | 478 | 585 | 756 | 894 | 1070 | 1310 | 1510 | 1850 | 57,9 | 54,0 | | | | | |
| | THF52624 | 129° | 132° | 135° | 1200 | 536 | 657 | 848 | 1000 | 1200 | 1470 | 1700 | 2080 | 63,1 | 54,0 | | | | | |
| | THF56424 | 129° | 132° | 135° | 1290 | 575 | 704 | 909 | 1080 | 1290 | 1570 | 1820 | 2230 | 65,9 | 54,0 | | | | | |

$$\text{Débit (l}_{\min}) = K \text{ bar}$$

Matériaux standard: Laiton, fonte gris, acier et 1.4401 (316).

Revised 7/14/99